



PIANC

The World Association for Waterborne
Transport Infrastructure

Design of Navigation Locks



InCom Working Group Report N° 206 – 2025

PIANC InCom WG Report N° 206

Design of Navigation Locks

27 August 2025

PIANC has Technical Commissions concerned with inland waterways and ports (InCom), coastal and ocean waterways (including ports and harbours) (MarCom), environmental aspects (EnviCom) and sport and pleasure navigation (RecCom).

This report has been produced by an international Working Group convened by the Inland Navigation Commission (InCom). Members of the Working Group represent several countries and are acknowledged experts in their profession.

The objective of this report is to provide information and recommendations on good practice. Conformity is not obligatory and engineering judgement should be used in its application, especially in special circumstances. This report should be seen as an expert guidance and state-of-the-art on this particular subject. PIANC disclaims all responsibility in the event that this report should be presented as an official standard.

PIANC HQ
Simon Bolivarlaan 17
1000 Brussels | Belgium

<http://www.pianc.org>

VAT BE 408-287-945

ISBN 978-2-87223-057-0

© All rights reserved

Executive Summary

This document presents a detailed and modernised guide for the planning, design, construction, and maintenance of navigation locks. Initiated by PIANC's Working Group 206, the report updates best practices and technological advances since the previous edition in 1986, offering a robust framework for engineers, planners, and stakeholders.

Purpose and Scope:

- Update and unify global design practices for navigation locks.
- Address the growing complexity of lock infrastructure and evolving environmental and operational demands.
- Emphasise the critical role of locks in facilitating efficient, sustainable inland waterway transport.

Design Fundamentals:

The report outlines a comprehensive and phased approach to lock design:

- Concept Development: Establishes goals, cost-benefit analysis, and stakeholder alignment.
- Planning & Feasibility: Defines operational requirements and develops concept designs.
- Detailed Design: Finalises technical specifications, material selections, and risk mitigation plans.

Structural and Operational Components:

- Specifies strict construction criteria, including flatness of concrete surfaces and tolerances for formwork and joints.
- Details the integration of critical components such as expansion joints, valves, culverts, and access systems.
- Stresses ease of inspection and repair, with designs accommodating future maintenance without operational disruption.

Equipment and Safety Systems:

- Equipment such as bollards, ladders, signals, and guide structures are designed for operational efficiency and safety.
- Lock equipment must adapt to site-specific needs (e.g. water levels, traffic density).
- Protective measures include fall prevention, edge protection, and wall armouring.

Gate and Valve Engineering:

- Various gate types are analysed (mitre, single leaf, sector) for structural requirements and operational context.

- Material selection (steel, timber, aluminium, composites) is guided by performance and durability.
- Flow-induced vibrations and hydraulic load effects are considered during gate design.

Hydraulic and Environmental Considerations:

- Hydraulic systems are optimised for speed, safety, and control during filling/emptying cycles.
- Saltwater intrusion management is addressed through systems like bubble screens and flushing.
- Water conservation and water management strategies are incorporated into lock operation plans.

Construction Methods:

- Two main approaches: in-the-dry (cofferdams) and in-the-wet (prefabrication).
- Method selection is based on site conditions, environmental concerns, and project timelines.

Maintenance and Rehabilitation:

- Maintenance is planned at both routine and emergency levels.
- Rehabilitation strategies target aging infrastructure, with upgrades to modern standards and materials.
- Emphasis on safe access, inspection intervals, and the long-term durability of key components.

Conclusion:

The document serves as a definitive reference for modern navigation lock projects, balancing engineering rigour with environmental stewardship and long-term operational performance. It supports the development of lock systems that are adaptable, efficient, and aligned with future transportation demands.

TABLE OF CONTENTS EXECUTIVE SUMMARY 4

TABLE OF CONTENTS	6
LIST OF FIGURES	18
LIST OF TABLES	27
1 INTRODUCTION	29
1.1 Value of Navigation Locks	32
1.2 Other PIANC Reports	34
1.3 Structure of the Report	34
1.4 PIANC Working Group 206	35
1.4.1 Members of the Working Group	35
1.4.2 Reviewers	37
1.4.3 Meetings	37
1.4.4 Acknowledgements	37
2 PLANNING A NEW LOCK	39
2.1 Introduction	39
2.2 Design	42
2.2.1 Project Conception	42
2.2.2 Planning, Concept Design, and Feasibility Stage	43
2.2.3 Preliminary and Detailed Design Stages	44
2.3 Existing (and Future) Conditions	44
2.4 Functional and Design Requirements	45
2.5 Traffic Forecasts and Vessel Dimensions	46
2.5.1 Traffic Forecasts	46
2.5.2 Vessel Sizes	47
2.5.2.1 Inland Waterways: Design Vessels	47
2.5.2.2 Maritime Locks: Design Vessels	50
2.6 Lock Capacity	51
2.6.1 Introduction	51
2.6.2 Lock Cycle Time	52
2.6.3 Levelling Time	54
2.7 Lock Dimensions	54
2.7.1 General Dimensions	54
2.7.2 Channel Dimensions	54
2.7.3 Lock Chamber Dimensions	55
2.7.3.1 Inland Navigation Locks	56
2.7.3.2 Maritime Locks	57
2.7.4 Dimensions of Lock Approach Areas and Structures	58
2.7.5 Maximum Practical Lift Height	61
2.7.6 Depth at Locks	62
2.8 Lock Gate and Valve Options	63
2.9 Filling/Emptying Systems	63
2.10 Water Saving	65
2.11 Other Uses for Locks	66
2.12 Inland Locks and Maritime Locks	66
2.12.1 Inland Locks	66
2.12.2 Maritime Locks	67
2.13 Design Life	68
2.14 Availability and Reliability	68
2.15 Adaptability/Future-Proof Design	69
2.16 Environmental Impact and Sustainability	69
2.17 Aesthetics	70
2.18 Operations Documents	71
2.19 Rehabilitation of Existing Locks	71
2.20 Asset Management and Data Collection	71
2.21 Building Information Modelling (BIM)	71
2.22 Standardisation	72
2.23 Flood Defence	72

2.24	Legislation and Procedures	73
2.25	Quality Control and Commissioning	74
2.26	Checklist of Functional and Design Requirements	74
3	LOCK TYPES	81
3.1	Type 1 – Lock (Generic)	81
3.2	Type 2 – Lock with Chamber with Sloping Sides	83
3.3	Type 3 – Lock with Cross Wall	84
3.4	Type 4 – Lock with Intermediate Gate	85
3.5	Type 5 – Group of Locks or Lock Complex	86
3.6	Type 6 – Twin Locks.....	87
3.7	Type 7 – Ladder of Locks	88
3.8	Type 8 – Flight of Locks.....	90
3.9	Type 9 – Lock with Water Saving Basins	92
3.10	Type 10 – Guard Lock	92
4	CIVIL AND STRUCTURAL DESIGN	93
4.1	Introduction	93
4.2	Requirements.....	94
4.2.1	Main Dimensions	94
4.2.2	Design Life of the Structure	95
4.2.3	Local and Project-Specific Conditions	95
4.2.4	Water Management	96
4.2.5	Drainage and Maintenance Strategy.....	96
4.2.6	Requirements for Lock Operation.....	97
4.3	Design Basis.....	97
4.3.1	Safety Philosophy and Reliability.....	97
4.3.2	Load Factors and Combinations	98
4.3.3	Permanent Loads	99
4.3.4	Ground Effects	99
4.3.5	Water Loads	99
4.3.5.1	Water Scenarios	99
4.3.5.2	Groundwater	101
4.3.5.3	Hydrostatic Loads.....	102
4.3.5.4	Wave Loads	102
4.3.5.5	Other Considerations.....	102
4.3.5.6	Combining Hydraulic Loads.....	103
4.3.6	Live Loads.....	104
4.3.6.1	Surface Loads	104
4.3.6.2	Equipment.....	104
4.3.6.3	Operational Loads	104
4.3.6.4	Shrinkage and Creep	105
4.3.6.5	Environmental Loads.....	105
4.3.7	Seismic Loads.....	106
4.3.8	Accidental Loads	106
4.3.8.1	Ship Impact.....	106
4.3.8.2	Dropped Anchors.....	110
4.3.8.3	Sunken Ship.....	110
4.3.8.4	Hydraulic Loads.....	110
4.4	Geotechnics	111
4.4.1	Data Acquisition	111
4.4.2	Geotechnical Data	111
4.4.3	Geomechanical Properties	112
4.4.4	Calculation Method.....	113
4.4.5	Flocks Subjected to Mine Subsidence	115
4.4.6	Soil Liquefaction.....	116
4.4.7	Locks in Rock.....	117
4.4.7.1	Introduction	117
4.4.7.2	Lock Chambers	117
4.4.7.3	Hydraulic Aspects	120

4.4.7.4	Consideration in the Design	121
4.4.8	Locks in Soft Soils	124
4.4.8.1	Introduction	124
4.4.8.2	Soil Improvements	124
4.5	Geohydrology	127
4.5.1	Introduction.....	127
4.5.2	Preventing Seepage and Piping.....	127
4.5.3	Preventing Uplift.....	129
4.5.4	Geohydrologic Impact of the Surroundings	131
4.5.5	Data Collection	132
4.6	Structural Design.....	133
4.6.1	Typical Cross Section.....	133
4.6.2	Lock Heads.....	138
4.6.2.1	Gates, Operating Mechanisms, Equipment, and Services	139
4.6.2.2	Levelling Systems	140
4.6.2.3	Sediment Traps	141
4.6.3	Lock Chambers and Retaining Structures.....	141
4.6.3.1	U-Shaped Concrete Structure	141
4.6.3.2	Anchored Soil Retaining Walls	142
4.6.3.3	Cofferdams.....	143
4.6.3.4	Relieving Platforms	143
4.6.3.5	L-Walls.....	143
4.6.3.6	Green Chambers	144
4.6.4	Lock Floors	145
4.6.5	Joints and Joint Sealing	145
4.6.5.1	Principles	145
4.6.5.2	Construction with Joints.....	145
4.6.5.2.1	Joints in the Lock Chamber	146
4.6.5.2.2	Joints in Special Areas	146
4.6.5.3	Jointless Construction	146
4.6.6	Approach Structure and Guidance Structures	149
4.7	Sustainability	150
4.8	Interface Management.....	153
4.8.1	Integration of Gates and Dewatering Devices	153
4.8.1.1	Integration of Bearing and Load Transmission from the Gates to the Solid Structure.....	153
4.8.1.2	Integration of Bearing and Load Transmission from the Drive Systems to the Solid Structure	154
4.8.1.3	Built-in Parts in the Initial Concrete	155
4.8.1.4	Built-in Parts in the Sealing Concrete (Second Stage)	155
4.8.1.5	Additional Gate Equipment.....	157
4.8.1.6	Supply Lines.....	157
4.8.1.7	Ice Prevention System and Removal of Floating Debris	157
4.8.1.8	Ship Impact Protection of the Lower Gate	157
4.8.1.9	Integration of Inspection Gates.....	157
4.8.1.10	Facilities for Drainage	158
4.8.1.11	Tolerances in Solid Construction/Hydraulic Steel Construction.....	158
4.8.2	Integration of Filling/Emptying Systems	159
4.8.2.1	General Information on Filling/Emptying Systems.....	159
4.8.2.1.1	Main Features of the Different Systems	159
4.8.2.1.1.1	End Systems.....	159
4.8.2.1.1.2	Side Systems	159
4.8.2.1.1.3	Baseflow or Bottom Systems	159
4.8.2.1.2	Deposits.....	159
4.8.2.1.3	Solid Constructions for End Systems.....	160
4.8.2.1.3.1	Filling/Emptying via Gate Movement or Valves.....	160
4.8.2.1.3.2	Filling/Emptying via Gate Bypass Conduits.....	160
4.8.2.1.3.3	Longitudinal Channels with Fixtures for Valves and Emergency Closures	161

4.8.2.1.3.4	Longitudinal Culverts and Baseflows with Fixtures for Valves and Emergency Closures	162
4.8.2.1.4	Special Requirements for the Solid Components of Filling/Emptying Systems	162
4.8.2.1.4.1	Geometry: Cross Section Design and Routing	162
4.8.2.1.4.2	Design in the Area of Expansion Joints	163
4.8.2.2	Incorporation of the Closure Elements into the Solid Construction	163
4.8.2.2.1	Arrangement of Valves	163
4.8.2.2.2	Barrier for Drainage	163
4.8.2.3	Maintenance of Filling/Emptying Systems in the Solid Construction	163
4.8.2.3.1	Maintenance and Inspection	163
4.8.2.3.2	Repair	164
4.8.3	Integration of Lock Equipment	164
4.9	Impact of Construction Methods	164
4.10	Design for Inspection and Maintenance	165
5	EQUIPMENT FOR LOCK WALLS AND APPROACHES	167
5.1	General	167
5.1.1	Goals, Functions, and Types of Equipment	167
5.1.2	Adaptations to Situations	168
5.1.3	Safety and Security Equipment	169
5.1.4	Typical Layout of Lock Equipment	170
5.1.5	Maintenance Space Requirements	170
5.2	Equipment Protecting Operating and Structural Facilities	170
5.2.1	Risk of Falling	170
5.2.2	Edge Protection	171
5.2.2.1	Corner Protection	171
5.2.2.2	Expansion Joints	173
5.2.3	Wall Armouring and Fenders	173
5.2.3.1	General Description	173
5.2.3.2	Wheel Fenders	177
5.2.3.3	Floating Fenders	178
5.2.3.4	Donut Fenders	179
5.2.3.5	Wall Armouring	179
5.2.3.6	Lessons Learned from Recent Projects	181
5.2.4	Protection of Gates Against Vessel Impacts	181
5.2.4.1	General	181
5.2.4.2	Reasons to protect Gates	181
5.2.4.3	Types of Protection Equipment	183
5.2.5	Fire Protection	184
5.2.6	Frost Protection	185
5.3	Equipment to Facilitate Lock Operations	185
5.3.1	Bollards and Other Mooring Equipment	185
5.3.1.1	General	185
5.3.1.2	Surface and Coping Bollards on Platforms	187
5.3.1.3	Floating Bollards	187
5.3.1.4	Check Posts	188
5.3.1.5	Mooring Equipment for Maintenance Work	188
5.3.1.6	Mooring Equipment for Sport and Leisure Shipping	189
5.3.2	Hands Free Mooring	189
5.3.3	Tow Haulage Units and Travelling Kevel (USA)	191
5.3.3.1	Tow Haulage Units	191
5.3.3.2	Traveling Kevels (USA)	193
5.3.4	Recent Lessons Learnt	194
5.3.5	Tug Assisted Locking (Panama, Large Locks)	195
5.3.6	Ladders	196
5.3.7	Illumination of Lock Basin and Entry Areas	197
5.3.8	Signalling	198
5.3.8.1	Signs	198
5.3.8.2	Light Signals	199

5.3.8.3	Marks	200
5.3.9	Operation and Communication Devices	202
5.4	Specific Equipment for Recreational Locks	202
6	GATES, VALVES, AND TEMPORARY CLOSURE STRUCTURES.....	204
6.1	Overview	204
6.1.1	Materials and Fabrication Techniques	219
6.1.1.1	Timber Advantages and Disadvantages	220
6.1.1.2	Steel Advantages and Disadvantages.....	221
6.1.1.3	Aluminium Advantages and Disadvantages.....	221
6.1.1.4	Composite Materials Advantages and Disadvantages	221
6.1.1.5	Typical Fabrication Quality Control Requirements	224
6.1.1.6	Commissioning Requirements.....	225
6.1.2	Typical Loading.....	226
6.1.3	Operating Machinery	228
6.1.4	Bearings	234
6.1.5	Water Sealing Design	235
6.1.6	Operations and Maintenance Considerations for the Design of Gates and Valves	239
6.1.7	Corrosion Protection of Steel Gates and Valves	240
6.1.8	Flow-Induced Vibrations of Gates and Valves	241
6.2	Gates Rotating on a Vertical Axis.....	244
6.2.1	Mitre Gate	244
6.2.1.1	Description	244
6.2.1.2	Framing and Load Path.....	246
6.2.1.3	Quoin/Mitre Blocks	251
6.2.1.4	Embedded Assemblies	253
6.2.1.5	Bearings.....	254
6.2.1.6	Operating Machinery	254
6.2.1.7	Advantages and Disadvantages.....	260
6.2.2	Single Leaf Gate	260
6.2.2.1	Description	260
6.2.2.2	Framing and Load Path.....	261
6.2.2.3	Embedded Assemblies	261
6.2.2.4	Bearings.....	262
6.2.2.5	Operating Machinery	262
6.2.2.6	Advantages and Disadvantages.....	262
6.2.3	Sector Gate.....	262
6.2.3.1	Description	262
6.2.3.2	Framing and Load Path.....	263
6.2.3.3	Embedded Assemblies	264
6.2.3.4	Bearings.....	265
6.2.3.5	Operating Machinery	265
6.2.3.6	Advantages and Disadvantages.....	268
6.3	Gates Rotating on a Horizontal Axis	268
6.3.1	Radial Gates Used as Lock Gates.....	268
6.3.1.1	Description	268
6.3.1.2	Framing and Load Path.....	269
6.3.1.3	Embedded Assemblies	269
6.3.1.4	Bearings.....	270
6.3.1.5	Operating Machinery	270
6.3.1.6	Advantages and Disadvantages.....	272
6.3.2	Rotary Segment Gate	272
6.3.2.1	Description	272
6.3.2.2	Framing and Load Path.....	276
6.3.2.3	Embedded Assemblies	277
6.3.2.4	Bearings.....	278
6.3.2.5	Operating and Machinery	278
6.3.2.6	Advantages and Disadvantages.....	280
6.3.3	Hinged Gates/Flap Gates	280

6.3.3.1	Description	280
6.3.3.2	Framing and Load Path.....	282
6.3.3.3	Embedded Assemblies	282
6.3.3.4	Bearings.....	283
6.3.3.5	Operating Machinery	283
6.3.3.6	Advantages and Disadvantages.....	283
6.4	Gates with Vertical Movement.....	283
6.4.1	Vertical Lift Gate.....	283
6.4.1.1	Description	283
6.4.1.2	Framing and Load Path.....	284
6.4.1.3	Embedded Assemblies	287
6.4.1.4	Bearings.....	288
6.4.1.5	Operating Machinery	288
6.4.1.6	Advantages and Disadvantages.....	293
6.5	Retractable Gates	293
6.5.1	Rolling Gates/Wheelbarrow Gates.....	293
6.5.1.1	Description	293
6.5.1.2	Framing and Load Path.....	297
6.5.1.3	Embedded Assemblies	298
6.5.1.4	Bearings.....	300
6.5.1.5	Operating Machinery	301
6.5.1.6	Advantages and Disadvantages.....	305
6.5.2	Hydraulic Sliding Gates	305
6.5.2.1	Description	305
6.5.2.2	Framing and Load Path.....	306
6.5.2.3	Embedded Assemblies	307
6.5.2.4	Bearings.....	307
6.5.2.5	Operating Machinery	308
6.5.2.6	Advantages and Disadvantages.....	309
6.6	Valves for Filling/Emptying Systems	309
6.6.1	General.....	309
6.6.2	Conventional Radial/Tainter Valves in Culvert Filling/Emptying Systems.....	310
6.6.2.1	Description	310
6.6.2.2	Framing and Load Path.....	310
6.6.2.3	Embedded Assemblies	311
6.6.2.4	Bearings.....	311
6.6.2.5	Operating Machinery	311
6.6.2.6	Advantages and Disadvantages.....	314
6.6.3	Reverse Radial/Tainter Valves in Culvert Filling/Emptying Systems	314
6.6.3.1	Description	314
6.6.3.2	Framing and Load Path.....	315
6.6.3.3	Embedded Assemblies	315
6.6.3.4	Bearings.....	315
6.6.3.5	Operating Machinery	315
6.6.3.6	Advantages and Disadvantages.....	317
6.6.4	Butterfly Valves.....	317
6.6.4.1	Description	317
6.6.4.2	Framing and Load Path.....	318
6.6.4.3	Embedded Assemblies	318
6.6.4.4	Bearings.....	318
6.6.4.5	Operating Machinery	318
6.6.4.6	Advantages and Disadvantages.....	318
6.6.5	Cylindrical Valves	319
6.6.5.1	Description	319
6.6.5.2	Framing and Load Path.....	322
6.6.5.3	Embedded Assemblies	322
6.6.5.4	Bearings.....	322
6.6.5.5	Operating Machinery	323

6.6.5.6	Advantages and Disadvantages.....	323
6.6.6	Stoney Gate Valves.....	323
6.6.6.1	Description	323
6.6.6.2	Framing and Load Path.....	324
6.6.6.3	Embedded Assemblies	325
6.6.6.4	Bearings.....	325
6.6.6.5	Operating Machinery	325
6.6.6.6	Advantages and Disadvantages.....	327
6.6.7	Vertical Lift Valves in Filling/Emptying Systems	327
6.6.7.1	Description	327
6.6.7.2	Framing and Load Path.....	329
6.6.7.3	Embedded Assemblies	329
6.6.7.4	Bearings.....	329
6.6.7.5	Operating Machinery	329
6.6.7.6	Advantages and Disadvantages.....	332
6.6.8	Vertical Lift Valves Within the Gate Structure	332
6.6.8.1	Description	332
6.6.8.2	Framing and Load Path.....	333
6.6.8.3	Embedded Assemblies	333
6.6.8.4	Bearings.....	333
6.6.8.5	Operating Machinery	333
6.6.8.6	Advantages and Disadvantages.....	334
6.7	Temporary Closure Structures	334
6.7.1	General.....	334
6.7.2	Lock Temporary Closure Structures – Bulkheads/Stoplogs	336
6.7.2.1	Description	336
6.7.2.2	Framing and Load Path.....	337
6.7.2.3	Embedded Assemblies	338
6.7.2.4	Bearings.....	338
6.7.2.5	Operating Machinery	338
6.7.2.6	Advantages and Disadvantages.....	338
6.7.3	Lifting Pivot Gates	339
6.7.3.1	Description	339
6.7.3.2	Framing and Load Path.....	340
6.7.3.3	Embedded Assemblies	340
6.7.3.4	Bearings.....	340
6.7.3.5	Operating Machinery	340
6.7.3.6	Advantages and Disadvantages.....	340
6.7.4	Trestle Panel Dewatering System	340
6.7.4.1	Description	340
6.7.4.2	Framing and Load Path.....	340
6.7.4.3	Embedded Assemblies	342
6.7.4.4	Bearings.....	342
6.7.4.5	Operating Machinery	342
6.7.4.6	Advantages and Disadvantages.....	342
6.7.5	Post Panel Systems.....	342
6.7.5.1	Description	342
6.7.5.2	Framing and Load Path.....	344
6.7.5.3	Embedded Assemblies	345
6.7.5.4	Bearings.....	345
6.7.5.5	Operating Machinery	345
6.7.5.6	Advantages and Disadvantages.....	345
6.7.6	Floating Caisson for Rolling/Sliding Gates	345
6.7.6.1	Description	345
6.7.6.2	Framing and Load Path.....	347
6.7.6.3	Embedded Assemblies	348
6.7.6.4	Bearings.....	348
6.7.6.5	Operating Machinery	348

6.7.6.6	Advantages and Disadvantages	348
6.7.7	Lock Emergency Closure Devices	348
6.7.7.1	Description	348
6.7.7.2	Framing and Load Path	348
6.7.7.3	Embedded Assemblies	348
6.7.7.4	Bearings	348
6.7.7.5	Operating Machinery	349
6.7.7.6	Advantages and Disadvantages	349
6.7.8	Floating Temporary Closure Structures	349
6.7.8.1	Description	349
6.7.8.2	Framing and Load Path	349
6.7.8.3	Embedded Assemblies	350
6.7.8.4	Bearings	350
6.7.8.5	Operating Machinery	350
6.7.8.6	Advantages and Disadvantages	350
6.7.9	Temporary Closure Structures for Filling/Emptying Systems	350
6.7.9.1	Description	350
6.7.9.2	Framing and Load Path	352
6.7.9.3	Embedded Assemblies	352
6.7.9.4	Bearings	352
6.7.9.5	Operating Machinery	352
6.7.9.6	Advantages and Disadvantages	352
7	HYDRAULICS	353
7.1	Introduction – Design Criteria	353
7.2	Approach Area Conditions and Adjacent Reaches	356
7.3	Filling/Emptying Systems	359
7.3.1	Description of the Types of Filling/Emptying (F/E) Systems	359
7.3.1.1	Filling/Emptying system Through or Around the Gate	359
7.3.1.2	Filling/Emptying System Using Longitudinal Culverts and Ports	360
7.3.1.3	Filling/Emptying System Through the Bottom of the Lock Chamber	361
7.3.2	Selection Process for Filling/Emptying Systems	362
7.3.3	Filling/Emptying Time Considerations and Valve Operations	364
7.3.4	Design of Inlet and Outlet Structure	365
7.3.5	Forces on Vessels and in the Mooring Lines	366
7.4	Specific Hydraulic Considerations	367
7.4.1	Cavitation	367
7.4.1.1	Definition and Effects	367
7.4.1.1.1	Detection of Cavitation During the Design Phase	369
7.4.1.1.2	Cavitation Coefficient	369
7.4.1.1.3	Global Approach	370
7.4.1.1.4	Cavitation Modelling	371
7.4.1.2	Design Solution to Avoid or Limit Cavitation Damage	371
7.4.1.2.1	Valve Selection	371
7.4.1.2.2	Deepen the Valve	371
7.4.1.2.3	Shape of the Culvert	371
7.4.1.2.4	Materials and Surface Protection	372
7.4.1.2.5	Valve Opening Schedule	372
7.4.1.2.6	Flow Aeration	372
7.4.1.2.7	Inspection and Repair	373
7.4.2	Air Entrainment	373
7.4.3	Piston Effects	375
7.4.3.1	Introduction	375
7.4.3.2	Rolling Gates	375
7.4.3.3	Vessels Entering or Leaving Locks	377
7.5	Other Usages for Locks	378
7.5.1	Lock Used as Fish Pass	378
7.5.2	Locks Used for Flood Discharge or Flushing	378
7.6	Hydraulic Design Methods	380

7.6.1	Overview	380
7.6.2	Engineering and Analytical Approaches	381
7.6.3	Numerical Models.....	381
7.6.3.1	1-D Models	381
7.6.3.2	2-D Models	383
7.6.3.3	3-D Models	383
7.6.3.4	Navigation Simulation.....	385
7.6.4	Physical Models.....	387
7.6.5	Hybrid Models	389
7.6.6	Conclusion.....	389
7.7	Field Measurements as a Design Tool for Adjustments and Commissioning	390
7.7.1	Introduction.....	390
7.7.2	Valve Opening Schedule	391
7.7.3	Filling/Emptying Hydrographs.....	391
7.7.4	Water Slope in the Lock Chamber, Vessel Movement and Mooring Line Forces	392
7.7.4.1	Water Slope	392
7.7.4.2	Vessel Movements	394
7.7.4.3	Forces in the Mooring Lines	395
7.7.5	Head Loss Coefficients in the Culverts and at the Valves.....	395
7.7.6	Cavitation Level.....	396
7.7.7	Vibration	397
7.7.8	Wave Amplitude in the Downstream and Upstream Reaches	398
7.7.9	Velocity Field in Critical Areas	399
7.7.10	Emergency Stop of the Levelling Process	399
7.7.11	Watertightness of Gates and Valve Seals.....	400
7.7.12	Lock Operation procedures	401
7.8	Hydraulic Loads on Lock Gates	401
7.8.1.1	Hydraulic Loads on Closed Lock Gates.....	401
7.8.1.2	Static Pressure Differences	402
7.8.1.3	Wind and/or Swell Waves.....	402
7.8.1.4	Translatory Waves.....	402
7.8.1.5	Vertical Stability Under Wave Loading	403
7.8.1.6	Propeller Jets.....	403
7.8.2	Hydraulic Loads on Open Lock Gates	403
7.8.3	Hydraulic Loads During Gate Opening or Closing Operation.....	404
7.8.3.1	Waves (Wind Waves, Sink and Surge Waves)	404
7.8.3.2	Head Differences (Residual Head, Density Differences, Surge Waves)	404
7.8.3.3	Hydrodynamic Forces from Movement	404
7.9	Hydraulic Loads on Lock Valves	404
7.9.1	Introduction.....	404
7.9.2	Hydrostatic Loads	405
7.9.3	Stationary Hydrodynamic Loads.....	405
7.9.4	Transient Hydrodynamic Loads	407
8	WATER SAVING SYSTEMS	409
8.1	Needs for Saving Water	409
8.2	Water Saving Basins	410
8.3	Fundamentals of Water Saving Basins	410
8.3.1	Levelling Process.....	412
8.3.2	Saving Rate	413
8.3.3	Ways to Optimise the Levelling Process	414
8.3.3.1	Geometry.....	414
8.3.3.2	Adjusting the Levels	414
8.3.3.3	Operation.....	415
8.3.4	Effect on Water Saving Basins on Salt Intrusion	415
8.4	Design Process.....	416
8.5	Examples	416
8.5.1	Lock Minden.....	416
8.6	Other Ways of Saving Water	419

8.6.1	Twin Locks.....	419
8.6.2	Step Locks.....	419
8.6.3	Locks with Intermediate Gates	421
8.6.4	Ship Lifts.....	421
8.6.5	Water Management	422
8.6.6	Pumping Stations	423
9	DENSITY CURRENTS AND SALTWATER INTRUSION AT SEA LOCKS	424
9.1	Introduction	424
9.2	Effect of Salt Water on Lock Operations.....	424
9.2.1	Density Currents	424
9.2.2	Entering and Exiting the Lock	425
9.2.2.1	Lock Exchange	425
9.2.2.2	Entering the Lock.....	426
9.2.2.3	Exiting the Lock.....	427
9.2.3	During Levelling.....	427
9.2.4	At the End of Levelling	430
9.2.4.1	Water Level Difference.....	430
9.2.4.2	Translatory Waves.....	432
9.2.4.3	Choice of Vertical Location of the Levelling Opening	432
9.2.4.4	Water Level Difference for Opening the Gate	433
9.3	Saltwater Intrusion at Locks	433
9.3.1	Mitigation Measures	435
9.3.1.1	Salt Barrier Systems	435
9.3.1.2	Flushing	436
	Salt Screen.....	436
9.3.1.3	Saltwater Substitution Filling/Emptying Systems.....	439
9.3.1.4	Control of Lock Operations.....	440
9.3.2	Summary.....	442
9.4	Special Design Considerations for New Sea Locks	442
10	CONTROL SYSTEMS AND LOCK OPERATIONS	444
10.1	General	444
10.2	Control Systems	444
10.2.1	Relay-Based Systems	445
10.2.2	PLC-Based Systems	446
10.2.3	Centralised Control	447
10.2.4	Remote Control	447
10.2.5	Automated Control.....	448
10.2.6	Safety Interlocking Systems.....	449
10.2.7	Human Machine Interfaces (HMI)	451
10.2.8	Process Control System (Supervisory Control and Data Acquisition System (SCADA)) ..	452
10.3	Communications/Coordination	452
10.3.1	Radio – VHF Portable Marine Radios	452
10.3.2	Vessel Self-Spotting.....	452
10.3.3	Television Equipment	453
10.4	Security at the Lock.....	454
10.4.1	Security Management	454
10.4.2	Personnel Security.....	454
10.4.3	Security Forces/Security Training	454
10.4.4	Physical Security.....	454
10.4.5	Information and Communications Technology Systems, Data, and Records Security...	454
10.4.6	Security Strategy	455
10.4.7	Perimeter Fencing	455
10.4.8	Access Control.....	455
10.4.9	Security Reporting Stations	456
10.4.10	Security Lighting.....	456
10.5	Training Simulator for Lock Operator	456
10.5.1	Training Simulator for Lock Operator	456
10.5.1.1	Background	456

10.5.1.2	Control System Integration	457
10.6	Ice Control at Locks	459
10.6.1	Ice Booms.....	461
10.6.2	Air Bubbles and Air Curtains	462
10.6.3	Air Bubbler System Design.....	464
10.6.4	Air Bubbler Orifice Design	466
10.6.5	Soo Locks.....	467
10.6.6	Flushing Valves	469
10.6.7	Management of Ice Buildup on Solid Surfaces	470
10.6.7.1	Heating Components.....	470
10.6.7.2	Heated Panels	470
10.6.7.3	Scraping ice.....	471
10.6.8	Freeing Gates from Ice	472
10.6.9	Ice Repellent Coatings	474
11	CONSTRUCTION	475
11.1	Introduction	475
11.2	Construction Methods	475
11.2.1	In-the-Dry Construction	476
11.2.1.1	Types of Cofferdams.....	478
11.2.1.1.1	Cellular Cofferdams.....	478
11.2.1.1.2	Sheet Pile Walls.....	480
11.2.1.1.3	Combination Walls.....	480
11.2.1.1.4	Concrete Diaphragm Walls	481
11.2.1.1.5	Pneumatic Caisson Method	483
11.2.1.1.6	Prefabricated Local Coffe Boxes	484
11.2.1.1.7	Open Excavation.....	488
11.2.2	In-the-Wet Construction.....	489
11.2.2.1	Float-In Method	491
11.2.2.2	Lift-In Method.....	493
11.2.2.3	Other In-the-Wet Methods	502
11.2.2.3.1	Sliding Method	502
11.2.2.3.2	Hanging Form Method	504
11.3	Other Construction Considerations.....	505
11.4	Rehabilitation of Existing Locks.....	506
11.5	Commissioning.....	507
12	INSPECTION AND MAINTENANCE.....	509
12.1	Overview	509
12.2	Maintenance	509
12.2.1	Types of Maintenance	509
12.2.2	Maintenance Requirements.....	511
12.3	Inspection Strategy and Planning	512
12.4	Safety Inspection and Maintenance for Personnel	515
12.4.1	Lock Dewatering and Schedule	516
12.4.2	Predicting Performance of Existing Lock Systems and Components.....	517
12.4.3	Critical Lock Components for Inspection.....	518
12.4.4	Hydraulic Steel Structures.....	521
12.4.4.1	Temporary Closure Structures	521
12.4.4.2	Lock Gates used for Navigation	521
12.4.4.3	Lock Gates/Valves used for Filling/Emptying Systems.....	522
12.4.5	Hydraulic Concrete Structures	523
12.4.6	Concrete Access/Control Structures.....	524
12.4.7	Electrical Systems.....	524
12.4.8	Mechanical Systems.....	528
12.5	Reliability Analysis for Mechanical and Electrical Equipment	531
12.5.1	Hazard Curves and Reliability Function.....	532
12.6	Asset Management	535
12.7	Service Level	537
12.8	Inspection to Support Asset Management Systems and Investment Planning	539

12.8.1.1	Structural Health Monitoring.....	539
12.8.1.2	Electrical and Mechanical Output Monitoring.....	540
13	REHABILITATION AND MODIFICATION STRATEGIES	541
13.1	Introduction	541
13.1.1	Reasons for Rehabilitation	542
13.1.1.1	Improve Condition and Performance	542
13.1.1.2	Modernisation.....	542
13.1.1.3	New Regulations, Standards or Requirements.....	542
13.1.2	Reasons for Modification	543
13.1.2.1	Lock Enlargement	543
13.1.2.2	Lock Chamber Reduction.....	545
13.2	Structural Rehabilitation.....	546
13.2.1	Concrete Rehabilitation	546
13.2.1.1	Concrete Material Considerations.....	549
13.2.1.2	Lock Wall - Top Horizontal Reconstruction (Resurfacing)	550
13.2.1.3	Lock Wall Vertical Surface Resurfacing	550
13.2.1.4	Lock Guide Wall Rehabilitation and Replacement.....	554
13.2.1.5	Lock Gate Anchorage Replacement.....	555
13.2.1.6	In-the-Wet Repairs.....	557
13.2.1.7	Concrete Demolition Techniques.....	557
13.2.1.8	Challenges of Placing New Concrete Against Old Concrete	560
13.2.2	Steel Rehabilitation.....	561
13.2.2.1	Coating System Rehabilitation	562
13.2.2.2	Cathodic Protection	563
13.2.2.3	Steel Member Rehabilitation Techniques	565
13.3	Mechanical and Electrical Rehabilitation	566
13.3.1	Electrical Rehabilitation	567
13.3.1.1	Rewiring	567
13.3.1.2	Upgrading Control Systems.....	567
13.3.1.3	Upgrading Industrial Automation (IA) Software	568
13.3.2	Mechanical Rehabilitation	569
13.3.2.1	Rehabilitating Machinery	569
13.3.2.2	Design Guidance Changes since Original Design	570
13.3.2.3	Changing Machinery (Electromechanical to Hydraulic, etc.).....	570
13.4	Foundation Rehabilitation	571
13.4.1	Assessment of Foundation Conditions.....	571
13.4.2	Stabilisation	571
13.4.3	Scour Protection	571
13.4.4	Reducing Risk During Lock Dewatering	571
13.5	Rehabilitation Techniques in a Space-Constrained Waterway	572
13.5.1	Scheduling and Phasing of Rehabilitation Work	573
13.5.2	Navigation Restrictions and Limited Closures	574
13.5.3	Localized Dewatering Structures	574
13.5.4	Whole Lock Dewatering	578
13.6	Commissioning Rehabilitated Components.....	580
14	REFERENCES.....	581
	APPENDIX A: TERMS OF REFERENCE	594
	APPENDIX B: GLOSSARY AND ABBREVIATIONS.....	596
B.1	Lock Parts and Terminology	596
B.2.	Glossary	599
B.3.	Abbreviations.....	603
	APPENDIX C: TABLE OF RELEVANT PIANC PUBLICATIONS.....	604

LIST OF FIGURES

Figure 1.1: Schematic of a lock and dam (barrage)	29
Figure 1.2: Panama Canal locks, Autoridad del Canal de Panamá (ACP) (Panama)	30
Figure 1.3: Terneuzen Locks, Nieuwe Sluis Terneuzen/Paremovi (the Netherlands)	30
Figure 1.4: Locks of Lanaye (Belgium)	31
Figure 1.5: Filling/emptying system, Marmet Locks and Dam (USA)	31
Figure 1.6: Sault Ste. Marie Locks and Dam(USA)	32
Figure 1.7: Waterways transportation can ease traffic congestion	34
Figure 1.8: Working Group 206, Terneuzen Lock (the Netherlands)	38
Figure 2.1: Large sea lock, Antwerp – Berendrecht Lock (Belgium)	39
Figure 2.2: Leisure craft, Grevelingen Lock, Bruinisse (Netherlands)	40
Figure 2.3: Leisure craft, Hollerich Lock, River Lahn (Germany)	40
Figure 2.4: Commercial and recreational navigation together, Elbe-Lübeck-Canal (Germany)	47
Figure 2.5: Lock cycle time operations	53
Figure 2.6: Lock chamber clearance, West lock Terneuzen (the Netherlands)	55
Figure 2.7: Schematic representation of a lock with holding basin.....	59
Figure 2.8: Typical approach area inland locks, Rothersee (Germany)	59
Figure 2.9: Lead-in jetties, Bristol (UK)	61
Figure 2.10: High lift locks, Three Gorges (China).....	62
Figure 2.11: Turbulence when filling between gates.....	64
Figure 2.12: F/E systems: through-gate sluices	64
Figure 2.13: F/E culverts: intake and chamber outlets on either side of gate docking chambers	65
Figure 3.1: Typical (generic) lock	81
Figure 3.2: Auvelais Lock, River Sambre (Belgium)	82
Figure 3.3: Type 2 lock with sloping sides.....	83
Figure 3.4: Lock with sloping sides; grass-sided lock, Visartsluis, Zeebrugge (Belgium) and Garston Lock (UK)	83
Figure 3.5: Type 3 lock with cross wall.....	84
Figure 3.6: Lock with cross wall, 4 th lock of Lanaye, Albert Canal (Belgium-the Netherlands)	84
Figure 3.7: Type 4 lock with intermediate gate.....	85
Figure 3.8: Type 5 group of locks or lock complex	86
Figure 3.9: Ivoz-Ramet lock complex, River Meuse (Belgium)	86
Figure 3.10: Type 6 twin locks.....	87
Figure 3.11: Type 7 ladder of locks	88
Figure 3.12: Ladder of locks, Three Gorges Dam (China).....	88
Figure 3.13: Ladder of locks, Bingley Five-Rise (UK)	89
Figure 3.14: Type 8 flight of locks	90
Figure 3.15: Flight of locks Caen Hill (UK)	90
Figure 3.16: Flight of locks Caen Hill (UK)	91
Figure 3.17: Type 9 lock with water saving basins.....	92
Figure 3.18: Type 10 guard lock.....	92
Figure 4.1: IJmuiden Locks (NL).....	93
Figure 4.2: Normal up to highest navigation levels.....	100
Figure 4.3: Lowest water levels	100
Figure 4.4: Accidental and/or exceptional levels	100
Figure 4.5: Safety overflow	101

Figure 4.6: Example of load configuration in a twin lock.....	101
Figure 4.7: Distribution of bending moments (stiff/soft underground conditions)	114
Figure 4.8: Transverse earthquake.....	117
Figure 4.9: High lift rock, Ust-Kamenogorsk (Kazakhstan)	123
Figure 4.10: Drainage galleries in Valeira lock	123
Figure 4.11: Vertical, inclined (prestressed) and dead anchors	124
Figure 4.12: Longitudinal rupture of the floor slab in Auvélais (Sambre, Belgium)	129
Figure 4.13: Underground water management	131
Figure 4.14: Lock Maasbracht (the Netherlands)	133
Figure 4.15: Decision tree	134
Figure 4.16: U-shape	136
Figure 4.17: Translational balance of lock sidewalls, cofferdams (top), ribs (left), rods (right)	137
Figure 4.18: Perforated floor.....	137
Figure 4.19: Rolling gate recesses, Nieuwe Sluis Terneuzen (the Netherlands)	139
Figure 4.20: Rach Chanh Lock (Vietnam)	144
Figure 4.21: Lock chamber, Zeesluis IJmuiden (the Netherlands)	148
Figure 4.22: Flexible guidance structures, Volkerak Sluizen (the Netherlands)	149
Figure 4.23: Flexible guidance structures, Oranjesluizen Amsterdam (the Netherlands)	149
Figure 4.24: Floating guidance structures, Beatrixsluis (the Netherlands).....	149
Figure 4.25: Lock of Ivoz-Ramet (Belgium)	150
Figure 4.26: The potential chance to influence the degree of environmental impact E, throughout the life cycle of the concrete structure	151
Figure 4.27: Lower anchor of the flap gate, Ivoz-Ramet (Belgium)	156
Figure 4.28: Terneuzen lock complex (the Netherlands)	165
Figure 5.1: Typical layout of lock equipment.....	170
Figure 5.2: Guard rail, Lanaye locks, Meuse River (BE), Zebra ground marking, Méricourt lock (France)	171
Figure 5.3: Horizontal edge protection, Gambsheim lock, Rhine River (France)	172
Figure 5.4: Cross cut of upper head- Geisling lock, Danube River (Germany)	172
Figure 5.5: Lead-in structure, Brunsbüttel (Germany)	174
Figure 5.9 : Canal wheel fender (Panama)	177
Figure 5.11: Donut fender to protect lock entrance, Port of Bremen (Germany).....	179
Figure 5.12: Sheet pile fenders, Méricourt lock 1, Seine River (France)	180
Figure 5.13: Timber beam fenders on a sheet pile wall, Méricourt lock 1, Seine River (France)	181
Figure 5.14: Shock absorbing device on downstream gate, lock of Don, Deule River (France)	184
Figure 5.15: Protection cable and its removing device. Lock of Heidelberg, Neckar River, (Germany)	184
Figure 5.16: Extracts of typical recessed bollard	187
Figure 5.17: Floating bollard with guiding structure next to recessed fixed bollard, Oberhausen (Germany)	188
Figure 5.19: Typical arrangement of MoorMaster systems at St. Lawrence Seaway lock (Canada)	190
Figure 5.23: Travelling kevel	193
Figure 5.24: Parallel and perpendicular ladders in lock, Heidelberg (Germany)	197
Figure 5.27: Camera views alongside a vessel entering a lock	201
Figure 6.1: Mitre gate in the closed/mitred position.....	205
Figure 6.2: Kattendijk lock, during installation Antwerp (Belgium)	206
Figure 6.3: Scaldis lock, during installation 2014, Ghent, Flanders (Belgium)	206
Figure 6.4: Sector gate in closed position (Thomas J. Obrien Lock and Dam)	207
Figure 6.5: The Dalles upstream radial navigation lock gate in closed position with dewatered lock (USA) 207	

Figure 6.6: Rotary segment gate, Niederfinow lock ship lift (Germany).....	208
Figure 6.7: Hinged crest/flap gate, Albert-Canal, Flanders (Belgium)	208
Figure 6.8: Hinged crest/flap gate being placed, Albert-Canal, Flanders (Belgium)	209
Figure 6.9: Ice Harbor vertical lift gate, raised position to allow vessels to travel beneath (USA)	209
Figure 6.10: New sea lock, IJmuiden (the Netherlands)	210
Figure 6.11: Sliding lock gate utilising hydrofeet, Prins Willem Alexander (the Netherlands)	210
Figure 6.12: Conventional radial Tainter valve (USA)	211
Figure 6.13: Reverse radial/Tainter valve from above, The Dalles (USA)	211
Figure 6.14: Butterfly-valve downstream side 16m-lock, Albert-canal, Flanders (Belgium)	212
Figure 6.15: Marmet lock Stoney valve (USA)	212
Figure 6.16: Vertical lift valve in fabrication (USA)	213
Figure 6.17: Vertical lift valve in culvert, Lanaken, Flanders (Belgium)	214
Figure 6.18: Vertical lift valve, IJmuiden rolling gate (the Netherlands)	214
Figure 6.19: Navigation lock stoplogs/bulkheads with a centre post arrangement.....	215
Figure 6.20: Lock of Evergem, lock opening temporary closure structures (Belgium)	215
Figure 6.21: Temporary closure system "Schönscher Verschluss", lock Kriegenbrunn, MDK (Main-danube-canal) (Germany).....	216
Figure 6.22: Post-panel-closure, view from lock side, lock Uelzen II (Germany)	216
Figure 6.23: Ship-door for lock of Lanaken/Neerharen (Belgium).....	217
Figure 6.24: Ship-door for locks of Albert Canal (Belgium)	217
Figure 6.25: Closure caisson Kieldrechtsluis, Antwerp (Belgium)	218
Figure 6.26: Timber mitre gate (during installation 2016) Verbindingsluis Brugge, Flanders (Belgium)	222
Figure 6.27: Steel mitre gate (during installation 2008) 25 m-lock of Evergem, Flanders (Belgium)	222
Figure 6.28: Steel weir (during installation 2015) Harelbeke, Flanders (Belgium)	222
Figure 6.29: Steel single leaf gate (during installation 2014) Scaldis lock, Gent, Flanders (Belgium).....	223
Figure 6.30: FRP mitre gate (the Netherlands)	223
Figure 6.31: Electromechanical drive lock 14, Mississippi River (USA)	229
Figure 6.32: Hydraulic drive system, Soo Locks (USA)	230
Figure 6.33: Graph of forces for Mississippi River lock 7 (USA).....	231
Figure 6.34: Electromechanical drive lock 2, Mississippi River (USA)	231
Figure 6.35: Hydraulic drive system, Evergem lock (Belgium).....	232
Figure 6.36: Mitre gate with electric lifting cylinder utilised as a drive	233
Figure 6.37: J-bulb bottom seal at pintle where seal is below bottom girder height, The Dalles (USA)	236
Figure 6.38: J-bulb seal	237
Figure 6.39: Rubber seal at the mitre sill.....	237
Figure 6.40: Typical mitre gate arrangement.....	245
Figure 6.41: Hydrostatic loads applied to a typical mitre gate leaf (the Netherlands)	246
Figure 6.42: Vertically framed mitre gate self-weight load path	247
Figure 6.43: Horizontally framed mitre gate load path	247
Figure 6.44: Mitre gate using folded structure construction, new Sülfeld lock, MLK (Mittellandkanal) (Germany)	248
Figure 6.45: Mitre gate using folded structure fabrication being installed, lock Marktbreit, Main (Germany)	249
Figure 6.46: Mitre gate equipped with agitators to keep the gate and niche areas free (ice, flotsam), Main River (Germany).....	250
Figure 6.47: Mitre gate with integrated composite filling and emptying valves, Offenbach Süd lock, Main (Germany)	250

Figure 6.48: Mitre gate using classical steel framed construction, Main (Germany).....	251
Figure 6.49: Mitre gate hydrostatic load transfer in typical mitre gates showing load transfer to quoin blocks	252
Figure 6.50: Hydraulic cylinder driving a rack and pinion at Robert Byrd lock (USA)	254
Figure 6.51: Drive and linkage (Panama)	256
Figure 6.52: Traditional Ohio River drive (USA)	256
Figure 6.53: Modified Ohio River linkage (USA)	257
Figure 6.54: Direct connected cylinder drive, Welland Canal (Canada)	258
Figure 6.55: Single Leaf Gate, Le Treport (France)	260
Figure 6.56: Drawing of single leaf gate, Le Treport (France).....	261
Figure 6.57: Aerial view of sector gate, Ecluse de Don (France)	263
Figure 6.58: Upstream view of sector gate during installation, Ecluse de Don (France)	264
Figure 6.59: Downstream view of sector gate during installation, Ecluse de Don (France)	264
Figure 6.60: LPV 149 sector gate, New Orleans (USA)	266
Figure 6.61: Hydraulic cylinder directly driving a sector gate, New Orleans (USA)	267
Figure 6.62: Upper St. Anthony Falls (USAF) lock gate, Mississippi River (USA)	269
Figure 6.63: Trunnion anchorage assembly, The Dalles navigation lock Tainter/radial valves (USA)	270
Figure 6.64: Ice Harbor navigation lock radial gate, Lower Snake River (USA)	271
Figure 6.65: Rotary segment gate, filling the lock chamber, lock Rehlingen (Germany)	273
Figure 6.66: Rotary segment with filling shell, upper gate lock Bolzum (Germany)	274
Figure 6.67: Rotary segment with filling shell, upper gate lock Bolzum (Germany)	274
Figure 6.68: Upper gate, rotary segment with tension gate arms, lock Uelzen II, ESK (Elbe Side Canal) (Germany)	275
Figure 6.69: Rotary segment gate, Niederfinow ship lift (Germany)	276
Figure 6.70: Radial segment gate internal framing during fabrication	277
Figure 6.71: Radial segment gate completed assembly.....	277
Figure 6.72: Radial segment gate in the up or closed position.....	278
Figure 6.73: Radial segment gate in the lowered or open position	278
Figure 6.74: Segment gate drive via electric lifting cylinder, drive pulley and torsion tube, Uelzen II lock, ESK, (Elbe Side Canal) (Germany)	279
Figure 6.75: Hinged gate, view from the upstream direction, old Wustervitz lock, EHK, (Elbe Havel Canal) (Germany)	280
Figure 6.76: Hinged gate, old Wustervitz lock, EHK (Elbe Havel Canal) (Germany)	281
Figure 6.77: Hinged gate, old Wustervitz lock, EHK (Elbe Havel Canal) (Germany)	281
Figure 6.78: Hinged gate at the 4 th lock of Lanaye (Belgium)	282
Figure 6.79: Hinged gate operating equipment.....	282
Figure 6.80: Vertical lift downstream navigation lock tied-arch gate skin plate, John Day (USA)	285
Figure 6.81: Vertical lift downstream navigation lock tied-arch gate downstream girders, John Day (USA)	286
Figure 6.82: Navigation lock tied arch vertical lift gate, John Day (USA)	286
Figure 6.83: Chain hoisted vertical lift gate in a dewatered lock.....	287
Figure 6.84: Vertical lift gate machinery and wire rope, Mel Price lock (USA)	289
Figure 6.85: Lockport lock wire rope sheave and hydraulic cylinder and crosshead	290
Figure 6.86: Navigation lock downstream vertical lift gate friction sheave hoisting system, John Day (USA)	291
Figure 6.87: Lifting cable and friction sheave for Ice Harbor lock (USA)	292
Figure 6.88: Rolling gates of the new third set of locks, Panama Canal (Panama)	294
Figure 6.89: Classical support system/wheelbarrow support system/sliding support system	295

Figure 6.90: Corridor between ballast and buoyancy tanks of new sealock IJmuiden (the Netherlands)	296
Figure 6.91: Cross-section of new sealock, IJmuiden (the Netherlands)	297
Figure 6.92: Oversea transportation can be a governing load case for the steel structure of the gate	298
Figure 6.93: Rolling gate embedded assemblies during construction of sealock, IJmuiden (the Netherlands)	299
Figure 6.94: Guide roller system of rolling gate Meppelerdiep (the Netherlands)	299
Figure 6.95: Stainless steel bearing supports in lock heads of new lock Terneuzen (the Netherlands)	300
Figure 6.96: Lower carriage new sealock, IJmuiden (the Netherlands)	301
Figure 6.97: Wire rope winch drive, north lock, IJmuiden (the Netherlands)	302
Figure 6.98: Wire rope drive machinery layout (the Netherlands)	303
Figure 6.99: Rack and pinion drive, new sealock IJmuiden (the Netherlands)	304
Figure 6.100: Sliding gate of the Prins Willem Alexander (PWA) lock in Amsterdam (the Netherlands)	306
Figure 6.101: Working principle hydrofoot PWA-lock (the Netherlands)	306
Figure 6.102: Hydrofeet mounted on both ends on the bottom of the gate (sealed for maintenance)	307
Figure 6.103: Hydrofoot bearing, Prins Willem Alexander (PWA) lock (the Netherlands)	308
Figure 6.104: Hydrofoot bearing cross-section (PWA-lock) (the Netherlands)	308
Figure 6.105: Typical lock filling and emptying system	309
Figure 6.106: Drive system for filling and emptying valve, Mississippi River (USA)	312
Figure 6.107: Culvert valve (radial gate) with wire rope lifting system, Mississippi River (USA)	312
Figure 6.108: Radial valve operating mechanisms	314
Figure 6.109: Bell crank assembly for reverse Tainter valve	316
Figure 6.110: Butterfly valve for the culverts of lock Lanaye (Belgium)	317
Figure 6.111: Butterfly-valve downstream side 16 m-lock, Albert Canal, Flanders (Belgium)	318
Figure 6.112: Partially opened outside-sliding cylindrical valve in conically shaped concrete funnel	320
Figure 6.113: Cylindrical valve partially open, Chittenden Lock, Seattle (USA)	320
Figure 6.114: Partially opened inside-sliding cylindrical valve at Chittenden lock, Seattle (USA)	320
Figure 6.115: Cylindrical valve	321
Figure 6.116: Cylindrical valve isometric view, embedded assemblies	322
Figure 6.117: Cylindrical valve, lock Hannover-Anderten (Germany)	323
Figure 6.118: Stoney gate roller train detail	324
Figure 6.119: Marmet lock Stoney valve, Chittenden lock, Seattle (USA)	325
Figure 6.120: Stoney gate drive system	326
Figure 6.121: Stoney valve crosshead assembly	326
Figure 6.122: Vertical lift valve in lock culvert in the closed and open position	328
Figure 6.123: New vertical slide valves for Chittenden lock, Seattle (USA)	329
Figure 6.124: New direct connected hydraulic cylinder, culvert valve being installed, Chittenden lock (USA)	330
Figure 6.125: Vertical lift valve isometric view	331
Figure 6.126: Vertical lift valves located within the gate body of a mitre gate	332
Figure 6.127: Evergem lock (Belgium)	334
Figure 6.128: First stoplog being installed to dewater upstream gate, The Dalles navigation lock (USA)	336
Figure 6.129: Stacked stoplogs, The Dalles navigation lock (USA)	336
Figure 6.130: Upstream stoplogs with lock dewatered for inspection, Bonneville navigation lock (USA)	337
Figure 6.131: Stoplog installation entering the stoplog slot on the north wall, The Dalles navigation lock (USA)	338
Figure 6.132: Operating bulkhead set into position, Olmsted lock, Ohio River (USA)	339
Figure 6.133: Temporary closure system 'Schönscher Verschluss', lock Kriegenbrunn, MDK (Germany)	341

Figure 6.134: Temporary closure system 'Schönscher Verschluss', on the Main (Germany)	342
Figure 6.135: Post-panel-closure, view from lock side, lock Uelzen II (Germany)	343
Figure 6.136: Post-panel-closure, view of the water side under construction, lock Uelzen II (Germany)	344
Figure 6.137: Floating caisson for rolling/sliding gates in floating position	346
Figure 6.138: Floating caisson for rolling/sliding gates ballasted and being installed	347
Figure 6.139: Floating navigation lock bulkhead, John Day (USA)	349
Figure 6.140: Typical filling and emptying culvert bulkhead	351
Figure 6.141: Typical lock culvert valve bulkhead, Bonneville navigation lock.....	351
Figure 7.1: Primary goals for hydraulic design.....	353
Figure 7.2: Approach areas adjacent to weir and hydropower station, Lehmen lock, Mosel (Germany)	357
Figure 7.3: Guard wall under construction, lock Ampsin, Meuse River (Belgium)	358
Figure 7.4: Example of F/E system through the gate (plan view and longitudinal section)	359
Figure 7.5: Example of F/E system around the gate (plan view and cross section)	360
Figure 7.6: Example of F/E system with longitudinal culverts and ports (plan view and cross section)	361
Figure 7.7: F/E system through the bottom with asymmetric distribution	362
Figure 7.8: F/E system through the bottom with symmetric distribution	362
Figure 7.9: Location for different cavitation issues.....	368
Figure 7.10: Damage to a concrete culvert	368
Figure 7.11: Global view from upstream of the opened valve	369
Figure 7.12: Damage located downstream of the valve in the upper part of the culvert	369
Figure 7.13: Evolution of the cavitation coefficient and the incipient damage cavitation thresholds	370
Figure 7.14: Arrangement with auto-aeration	373
Figure 7.15: Geysering from a valve shaft due to air entrainment, Anderten Lock (Germany)	374
Figure 7.16: Lock with acceptable air entrainment (left) near Bolzum, very high air entrainment (right) near Schwabenheim (Germany)	375
Figure 7.17: Forces on IJmuiden lock gate due to head difference and resistance in the gate (the Netherlands)	376
Figure 7.18: Lock opening the upper sector gates against the water pressure (Finland)	379
Figure 7.19: 1D network model of a filling system	382
Figure 7.20: Simulation of the filling through a longitudinal canal and filling nozzles	384
Figure 7.21: Transversal forces acting on a vessel computed with two different discretisation schemes	385
Figure 7.22: View of the bridge of a full mission simulator for inland navigation.....	386
Figure 7.23: Physical model of the lock Terneuzen (Deltares laboratory) (the Netherlands)	387
Figure 7.24: Physical model of the downstream outer harbor of a lock, (BAW laboratory)	387
Figure 7.25: Pressure gauges for free surface slope measurements	393
Figure 7.26: Total stations (left), Prism and GPS receiver installed on the vessel (right), Roselies lock (Belgium)	395
Figure 7.27: Installation of sensors in lock for hydraulic tests.....	396
Figure 7.28: Hydrophone and accelerometer to measure noise and vibration due to cavitation at the valve	397
Figure 7.29: Some pictures of vibration sensors implemented on the lock of Vallabrègues (France)	398
Figure 7.30: a) Time evolution of the waves in the downstream reaches and emptying discharge from the locks Lanaye 3 and 4 (Zd1 : 50 m, Zd2 : 500 m, Zd3 : 1200 m, Zd4 : 3200 m downstream) b) site configuration – downstream reach – Lanaye canal	399
Figure 7.31: Emergency stop at Ivoz-Ramet lock: (a) Levelling curve; and (b) water slope in lock chamber (Belgium).....	400

Figure 7.32: View on 3-D representation of a vertical lift valve from upstream (left) and downstream (right)	405
Figure 7.33: Flow paths for a vertical lift gate	406
Figure 7.34: Vertical hydraulic force on a vertical lift gate for different opening ratios (left) and the impact of gap width on the top for an opening ratio of 8.4 % (right)	407
Figure 8.1: Principles of water saving basins	410
Figure 8.2: Principles of the levelling process	412
Figure 8.3: Saving rate depending on the number of saving basins	413
Figure 8.4: Levelling process between saving basin and lock chamber	415
Figure 8.5: New lock Minden (Germany)	416
Figure 8.6: Representative cross section through the new lock Minden (Germany)	417
Figure 8.7: Longitudinal and horizontal cross section of through the new lock Minden (Germany)	417
Figure 8.8: Physical scale-model of the new lock Minden (Germany)	418
Figure 8.9: Numerical investigation of the filling nozzles for different Reynolds Numbers	418
Figure 8.10: Schematic sketch of a twin lock	419
Figure 8.11: Schematic sketch of a flight of locks	420
Figure 8.12: Schematic sketch of a lock ladder	420
Figure 8.13: Agua Clara locks (Panama)	421
Figure 8.14: Schematic sketch of a shiplift	422
Figure 9.1: Schematic representation of density currents while levelling in a sea lock	425
Figure 9.2: Density current in the scale model, new sea lock, IJmuiden shortly after opening the lock gate (the Netherlands)	426
Figure 9.3: Comparison of three tests with increasing density difference and with ship moored asymmetrically in the transverse direction of the lock	429
Figure 9.4: Pressure diagrams and resulting forces on the lock gate at the end of levelling	431
Figure 9.5: Principle of direct saltwater withdrawal at Terneuzen (the Netherlands)	437
Figure 9.6: Withdrawal culverts during construction at the Terneuzen lock (the Netherlands)	438
Figure 9.7: Principle of saltwater withdrawal from a salt pit	439
Figure 9.8: Lockage cycle of the large Krammer lock	440
Figure 10.1: Remote control use at VNF	449
Figure 10.2: Operation control centre (left) and lock schematic (right)	449
Figure 10.3: Interlock system diagram	450
Figure 10.4: HMI screen at St-Lawrence Seaway (Canada)	451
Figure 10.5: HMI screen Chittenden lock (USA)	451
Figure 10.6: Scanner providing the ship distance in the lock, St-Lawrence Seaway (Canada)	453
Figure 10.7: Display panel showing ship position in the lock, St-Lawrence Seaway (Canada)	453
Figure 10.8: Camera system	455
Figure 10.9: Training simulator workstation	458
Figure 10.10: Sample camera simulation bridge view	459
Figure 10.11: Sample camera simulation lock view	459
Figure 10.12: Iron ore freighter passing through Soo locks in winter (USA)	460
Figure 10.13: Example of ice boom arrangement, St. Marys River, Michigan (USA)	462
Figure 10.14: Definition sketch of an air screen in cross section	463
Figure 10.15: Ice conditions Soo locks and showing air bubbler system in operation (USA)	463
Figure 10.16: Plan view of a high-flow air screen system	464
Figure 10.17: Lock 8 air bubbler system layout dimensions in customary units (USA)	465
Figure 10.18: Air diffuser check valves	466

Figure 10.19: Soo locks compressed air plant (USA)	468
Figure 10.20: Soo locks steam plant (USA)	468
Figure 10.21: Soo locks ice flushing valves (USA)	469
Figure 10.22: Skimming ice over emergency bulkheads at New Cumberland lock, Ohio River (USA)	470
Figure 10.23: Tug scraping ice on lock wall at St-Lambert lock, St-Lawrence Seaway (Canada)	471
Figure 10.24: Excavator removing ice.....	472
Figure 10.25: De-icing mitre gates with portable steam, Côte Ste-Catherine lock, St-Lawrence Seaway (Canada)	473
Figure 10.26: De-icing mitre gates using cement truck with high pressure water, Côte Ste-Catherine lock, St-Lawrence Seaway (Canada)	474
Figure 11.1: Conventional equipment and methods for in-the-dry construction 1, Panama locks (Panama)	477
Figure 11.2: Conventional equipment and methods for in-the-dry construction 2, Panama locks (Panama)	478
Figure 11.3: Combined earthen and sheet pile cofferdam, Cardiff lock (UK)	478
Figure 11.4: Cellular cofferdam prior to lock construction, Olmsted locks (USA)	479
Figure 11.5: Cellular cofferdam during lock construction, Olmsted locks (USA)	479
Figure 11.6: Sheet pile wall cofferdam, Charleroi lock (USA)	480
Figure 11.7: Combination wall cofferdam, Brunsbüttel lock (Germany)	481
Figure 11.8: Concrete diaphragm wall, Terneuzen lock (the Netherlands)	482
Figure 11.9: Concrete diaphragm wall anchors, Terneuzen lock (the Netherlands)	483
Figure 11.10: Pneumatic caisson method, lock in Almere (the Netherlands).....	484
Figure 11.11: Prefabricated steel coffer box, Mississippi River lock 16 (USA)	485
Figure 11.12: Prefabricated steel coffer box, transporting on barge, Ohio River (USA)	486
Figure 11.13: Prefabricated steel coffer box, positioning on dam pier, Ohio River (USA)	487
Figure 11.14: Prefabricated steel coffer box, positioned on chamber face, Arkansas River (USA)	488
Figure 11.15: Lock construction in open excavation, DNC project (Vietnam)	489
Figure 11.16: Completed float-in guide walls, Olmsted locks (USA)	491
Figure 11.17: Transport of precast float-in concrete module, Braddock Dam (USA)	492
Figure 11.18: Casting yard used for the precast float-in concrete modules, Braddock Dam (USA)	492
Figure 11.19: Installation of a precast float-in concrete module, Braddock Dam (USA)	493
Figure 11.20: Schematic of lift-in precast concrete modules, Chickamauga lock (USA)	493
Figure 11.21: Architectural rendering of lift-in precast concrete modules, Chickamauga lock (USA)	494
Figure 11.22: Lift-in precast concrete modules at casting yard, Chickamauga lock (USA)	494
Figure 11.23: Transporting a lift-In precast concrete module, Chickamauga lock (USA)	495
Figure 11.24: Setting a lift-in precast concrete module, Chickamauga lock (USA)	495
Figure 11.25: Inside a dewatered lift-in precast concrete module, Chickamauga lock (USA)	496
Figure 11.26: Construction of a combination lock wall and cofferdam using lift-in precast concrete modules, Chickamauga lock (USA)	496
Figure 11.27: Construction of a combination lock wall and cofferdam using lift-in precast concrete modules, Chickamauga lock (USA)	497
Figure 11.28: Drawing of lift-in precast concrete modules on drilled shaft foundations, Chickamauga lock (USA).....	497
Figure 11.29: Completed combination lock wall and cofferdam, Chickamauga lock (USA)	498
Figure 11.30: Completed combination cofferdam, Chickamauga lock (USA)	498
Figure 11.31: Drawing of lift-in precast concrete modules, Kentucky lock (USA).....	499
Figure 11.32: Casting yard for lift-in precast concrete modules, Kentucky lock (USA).....	499

Figure 11.33: Gantry used for lift-in precast modules, Kentucky lock (USA)	500
Figure 11.34: Completed combination cofferdam, Kentucky lock (USA)	501
Figure 11.35: Lift-In precast/prestressed guide wall beams, Marnet lock (USA)	502
Figure 11.36: Schematic of proposed prefabrication shell with culvert, lock 25 (USA)	502
Figure 11.37: Schematic of proposed sliding method, Quesnoy-Sur-Deule lock (France)	503
Figure 11.38: Schematic of sliding method, Quesnoy-Sur-Deule lock (France)	503
Figure 11.39: Installation of hanging form on work platform supported by piles, Charleroi lock (USA)	504
Figure 11.40: Schematic of construction sequence using hanging forms, lock 25 (USA)	505
Figure 12.1: Type of maintenance	510
Figure 12.2: PF-interval	514
Figure 12.3: Climbers inspecting a large lift gate (USA)	519
Figure 12.4: Climber inspecting a lift gate in service (note water leakage underneath gate (USA)	520
Figure 12.5: Hazard function vs time	532
Figure 12.6: Sawtooth hazard function	533
Figure 12.7: Reliability function vs time	534
Figure 12.8: A process approach of maintenance	535
Figure 12.9: Alignment from service level agreement to maintenance tasks	538
Figure 13.1: Stratton lock chamber extension, Chicago area (USA)	544
Figure 13.2: Mississippi River, lock No. 25 extension (USA)	544
Figure 13.3: Proposed lock size reduction, Inglis lock, Florida (USA)	545
Figure 13.4: Proposed chamber narrowing (section), Kentucky River, lock no. 10 (USA)	546
Figure 13.5: Proposed chamber narrowing (plan), Kentucky River, lock no. 10 (USA)	546
Figure 13.6: Falling and rough concrete that can cause damage to vessels, lock 13, Mississippi River (USA)	547
Figure 13.7: Vertical crack in lock wall monolith cross-section shown in red, Holt lock (USA)	548
Figure 13.8: Section of typical lock wall concrete refacing	549
Figure 13.9: LaGrange lock rehabilitation 2020, Illinois waterway (USA)	551
Figure 13.10: Precast concrete stay-in-place forms speed the resurfacing of the vertical faces of the lock chamber at LaGrange lock rehabilitation 2020, Illinois waterway (USA)	551
Figure 13.11: Concrete repair, lock 3, Welland Canal, St. Lawrence Seaway (Canada)	552
Figure 13.12: Precast concrete wall panel elevation, cross-section and side edge taper, LaGrange lock (USA)	554
Figure 13.13: Elevation of installed precast concrete wall panel and horizontal cross section through panel showing how panel reinforcement is 'locked-in' to existing concrete wall, LaGrange lock (USA)	554
Figure 13.14: Exposed top of embedded mitre gate anchorage frame where only the pin plates (darker grey) need to be replaced to extend the life of the anchorage system, Peoria lock (USA)	556
Figure 13.15: Top-mounted retrofit of an embedded anchorage frame, plan view, lock 2, Mississippi River (USA)	556
Figure 13.16: Top-mounted retrofit of an embedded anchorage frame, elevation view, lock 2, Mississippi River (USA)	557
Figure 13.17: Blasting demolition of concrete	559
Figure 13.18: The use of GPS in removing concrete, St. Lawrence Seaway (USA)	560
Figure 13.19: Hydro-demolition machine, being used at lock 17 to remove old concrete from the lock walls, Mississippi River (USA)	560
Figure 13.20: Cracked resurfaced concrete, Starved Rock Dam (USA)	561
Figure 13.21: Galvanic anodes on a navigation lock sector gate, New Orleans (USA)	564
Figure 13.22: CFRP repair of crack (upper left), Old Hickory lock mitre gate (USA)	566

Figure 13.23: CFRP strengthening of severely corroded member, Boggs Dam Tainter gate (USA)	566
Figure 13.24: Relief wells (on lock floor near lock wall) and lock floor weep holes in use during lock 18 dewatering, Mississippi River (USA)	572
Figure 13.25: Close-up views of relief well heads with check valve and exterior locking flapper valve in use during lock 18 dewatering, Mississippi River (USA)	572
Figure 13.26: Drybox being lifted into place (left) and in place (right, below right corner) to enable dry, safe working on (in this case) the gate recess in the Netherlands	575
Figure 13.27: Drybox being lifted into place for the renewal of a thrust bearing, Terneuzen (the Netherlands)	576
Figure 13.28: Wall-mounted cofferbox supported vertically from top of lock wall, Lock 25, Mississippi River (USA)	577
Figure 13.29: Coffebox placed in the mid-width of the lock for maintenance on centre-post style lock dewatering structure, McClellan-Kerr Arkansas River navigation system (USA)	577
Figure 13.30: Sediment with decaying fish, Krammersluizen (the Netherlands)	579

LIST OF TABLES

Table 2-1: Proposal of classification of European inland waterways [PIANC WG 179, 2020]	49
Table 2-2: Typical barge and tug dimensions (USA)	50
Table 2-3: Typical design vessels for recent maritime lock projects	51
Table 2-4: Design rules for minimum and capacity locks respectively	56
Table 2-5: Dimensions of a Minimum Lock for inland navigation	56
Table 2-6: Indication of required inland navigation lock dimensions as function of navigation volume	57
Table 2-7: Typical design lives of lock components	68
Table 2-8: Functional and design requirements: checklist	80
Table 3-1: Type 2 lock – advantages and disadvantages	84
Table 3-2: Type 3 lock – advantages and disadvantages	85
Table 3-3: Type 4 lock – advantages and disadvantages	85
Table 3-4: Type 5 lock – advantages and disadvantages	86
Table 3-5: Type 6 lock – advantages and disadvantages	87
Table 3-6: Interconnected twin lock	87
Table 3-7: Type 7 lock – advantages and disadvantages	89
Table 3-8: Type 8 lock – advantages and disadvantages	91
Table 4-1: Example: Locks on Meuse River (BE): Energy = 97kJ	105
Table 4-2: Example: Temperature limits for locks designed in Belgium	106
Table 4-3: Indicative values for the dynamic forces due to ship impact on inland waterways	108
Table 4-4: Preliminary design barge impact forces (ONLY for reconnaissance stage) kips need to be multiplied by 4.45 to get kN	109
Table 4-5: Geotechnical parameters and methods in foundation design	112
Table 4-6: Example of characteristic soil values.	113
Table 5-1: Main choices of equipment according to lock type	168
Table 5-2: Table of equipment according to lock type	169
Table 5-3: Characteristics of a vessel impact on a fender	177
Table 5-4: Seagoing vessels arriving and departing between Ghent (Belgium) and Terneuzen Canal (the Netherlands)	196

Table 5-5: Use of tugs for lock passage, between Ghent (Belgium) and Terneuzen Canal (the Netherlands)	196
Table 6-1: Common gate/valve types used in lock structures	219
Table 6-2: Timber advantages and disadvantages	220
Table 6-3: Steel advantages and disadvantages	221
Table 6-4: Aluminium advantages and disadvantages	221
Table 6-5: Composite materials advantages and disadvantages	221
Table 6-6: Mitre gate advantages and disadvantages	260
Table 6-7: Single leaf gate advantages and disadvantages	262
Table 6-8: Sector gate advantages and disadvantages	268
Table 6-9: Radial gate advantages and disadvantages	272
Table 6-10: Rotary segment gate advantages and disadvantages	280
Table 6-11: Hinged gate advantages and disadvantages	283
Table 6-12: Vertical lift gates used for filling and emptying systems advantages and disadvantages	293
Table 6-13: Vertical lift gates used for lock gates advantages and disadvantages	293
Table 6-14: Rolling gates advantages and disadvantages	305
Table 6-15: Advantages and disadvantages of sliding gates compared to rolling gates	309
Table 6-16: Conventional radial valves advantages and disadvantages	314
Table 6-17: Reverse radial valve advantages and disadvantages	317
Table 6-18: Butterfly valve advantages and disadvantages	319
Table 6-19: Cylindrical valve advantages and disadvantages	323
Table 6-20: Stoney gate valves advantages and disadvantages	327
Table 6-21: Vertical lift valves in filling and emptying systems advantages and disadvantages	332
Table 6-22: Vertical lift valves within gate structures advantages and disadvantages	334
Table 6-23: Bulkhead/stoplog advantages and disadvantages	338
Table 6-24: Lifting pivot gates advantages and disadvantages	340
Table 6-25: Trestle panel system advantages and disadvantages	342
Table 6-26: Post panel systems advantages and disadvantages	345
Table 6-27: Floating caisson bulkhead for rolling and sliding gates advantages and disadvantages	348
Table 6-28: Lock emergency closure structures advantages and disadvantages	349
Table 6-29: Floating bulkhead advantages and disadvantages	350
Table 6-30: Filling and emptying culvert bulkhead advantages and disadvantages	352
Table 7-1: Recommended design depending on the head of the lock (China)	372
Table 12-1: Comparison between preventive and non-preventive maintenance	510
Table 12-2: Comparison of preventive and corrective maintenance	511
Table 12-3: Concise inspection strategy	515