



Approach Channels A Guide for Design



PTC B-30
Final report of the joint Working
Group PIANC and IAPH, in
cooperation with IMPA and IALA
Supplement to Bulletin no 95
(June 1997)

1. **INTRODUCTION**
2. **COMMERCIAL CONSIDERATIONS**
 - 2.1 Port as Interface
 - 2.2 Pressures on Approach Channel Design
 - 2.3 Cost/Benefit Analysis
 - 2.4 Environmental Impact
3. **APPROACH CHANNEL DESIGN METHODOLOGY**
 - 3.1 Data Collection, Design Tools and Experience
 - 3.2 Basic Definitions
 - 3.3 Stages of the Design Process
 - 3.4 Physical Environment Data

3.5	Alignment, Width and Depth
3.6	Aids to Navigation
3.7	Operational Limits
3.8	Marine Traffic and Risk Analysis
4.	THE DESIGN SHIP
4.1	The 'Design Ship Concept
4.2	Choice of the Design Ship
4.2.1	Basic Philosophy
4.2.2	Ship Type
4.2.3	Traffic Analysis
4.2.4	Design Ship Dimensions
5.	CONCEPT DESIGN
5.1	General
5.2	Channel Design
5.2.1	Alignment, Width and Depth
5.2.2	Alignment
5.2.3	Width Considerations
5.2.3.1	Basic Manoeuvrability
5.2.3.2	Environmental Factors
5.2.3.3	Aids to Navigation
5.2.3.4	Type of Cargo
5.2.3.5	Passing Distance
5.2.3.6	Bank Clearance
5.2.4	Depth Considerations
5.2.5	Bends
5.3	Channel Concept Design Method
5.3.1	Introduction
5.3.2	Depth
5.3.3	Width: Straight Sections
5.3.4	Bend Width and Radius
5.3.5	Alignment
5.3.6	Definitions and Notes for the Tables
5.3.6.1	Table5.1- Ship Manoeuvrability
5.3.6.2	Table5.2 - Channel, Fairway, etc.
5.3.6.3	Table5.3 – Passing Distance
5.3.6.4	Table5.4 – Bank Clearance
5.3.6.5	Berthing and Swinging Areas
5.4	Worked Examples
5.5	Data on Existing Approach Channels
6.	DETAILED DESIGN
6.1	General Methodology
6.2	Assessment of the Environment
6.2.1	General
6.2.2	Environmental Data
6.2.3	Field Data Collection Techniques, Analysis and Prediction
6.2.4	Monitoring and Marine Information Systems
6.3	Channel Alignment
6.3.1	General
6.3.2	Bend Configuration
6.3.3	Bend Marking
6.3.4	Bend Width Assessment
6.4	Channel Width
6.4.1	General
6.4.2	Shiphandling and Simulation
6.4.3	Use of Simulation for Channel Width
6.4.3.1	Real Time with Mariners; the 'Panel of Experts
6.4.3.2	Fast Time Simulation
6.5	Channel Depth
6.5.1	Introduction
6.5.2	Squat
6.5.2.1	Factors Influencing Squat
6.5.2.2	Recommendations for the Estimation of Squat
6.5.2.3	Calculation of Squat
6.5.2.4	Special Cases of Squat
6.5.3	Underkeel Clearance in Waves
6.5.3.1	Wave Spectrum
6.5.3.2	Vertical Motion of the Design Vessel
6.5.3.3	Allowable Maximum Vertical Motion

- 6.5.3.4 Safety Criteria and Decision Rules
- 6.5.4 Channel Depths in Muddy Areas
 - 6.5.4.1 Motivation
 - 6.5.4.2 Nautical Bottom Approach
 - 6.5.4.3 Mud Characteristics
 - 6.5.4.4 Criteria for Determination of Nautical Bottom
 - 6.5.4.5 Behaviour of Ships in Muddy Areas
 - 6.5.4.6 Recommendations for Channel Depth in Muddy Areas
- 6.6 Berthing and Swinging Areas
 - 6.6.1 Use of Simulations
 - 6.6.2 Berth Alignment
 - 6.6.3 Tug Sizing and Numbers
 - 6.6.4 Swinging Area Design
- 6.7 Operational Limits
 - 6.7.1 Tug and Mooring Boat Operations
 - 6.7.2 Pilot Boarding
 - 6.7.3 Fender Impact Velocities
 - 6.7.4 Astern Manoeuvres
 - 6.7.5 Moored Ship Movements
- 7. MARINE RISK AND SAFETY OF OPERATION**
 - 7.1 Introduction to Marine Risk
 - 7.1.1 Marine Risk
 - 7.1.2 Estimation of Marine Risk
 - 7.1.3 Risk Alleviation Methods
 - 7.2 Alleviation of Marine Risk
 - 7.2.1 Vessel Traffic Service(VTS)
 - 7.2.2 Operating Limits
 - 7.2.3 Rules of Operation
 - 7.2.4 Aids to Navigation
 - 7.2.5 Traffic Separation Schemes
 - 7.3 Collection of Data
 - 7.4 Traffic Planning and Traffic Simulation
 - 7.4.1 Introduction
 - 7.4.2 Traffic Flow Simulation Models
 - 7.4.3 Procedure for the Development of a Traffic Flow Model
 - 7.4.4 Boundary Conditions and Input Data
 - 7.4.5 Output
 - 7.4.6 Evaluation of Simulation Results
 - 7.5 Pilotage Considerations
 - 7.5.1 General
 - 7.5.2 Pilot Variability
 - 7.5.3 Pilot Boarding Areas
 - 7.5.4 Anchoring Areas and Lay-by Berths
 - 7.5.5 Pilot Numbers
 - 7.5.6 Safety Aspects
 - 7.6 Safety Criteria
 - 7.6.1 General
 - 7.6.2 Primary and Secondary Criteria
 - 7.6.3 Risk Criteria
 - 7.6.4 Rudder Activity Criteria
 - 7.6.5 Width Criteria
 - 7.6.6 Depth Criteria
 - 7.6.7 Alignment Criteria
- 8. METHODOLOGY OVERVIEW: THE MARINE IMPACT ASSESSMENT**
 - 8.1 General Overview
 - 8.2 The Marine Impact Assessment
- 9. TERMS OF REFERENCE**
- 10. REFERENCES**
- 11. GLOSSARY**
- 12. LIST OF SYMBOLS**

APPENDIX A: Analysis of Existing Approach Channel Widths

APPENDIX B: Typical Ship Dimensions

APPENDIX C: Prediction of Squat

APPENDIX D: Water Depths in Muddy Areas: The Nautical Bottom Approach